

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

**Product Description:** Nickel plating solution, electroless, ammonia free  
**Cat No. :** 44070

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Laboratory chemicals.  
**Uses advised against** No Information available

### 1.3. Details of the supplier of the safety data sheet

**Company**  
Avocado Research Chemicals Ltd.  
(Part of Thermo Fisher Scientific)  
Shore Road, Heysham  
Lancashire, LA3 2XY,  
United Kingdom  
Office Tel: +44 (0) 1524 850506  
Office Fax: +44 (0) 1524 850608

**E-mail address** begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

**Poison Centre - Emergency information services**  
**Ireland** : National Poisons Information Centre (NPIC) -  
**01 809 2166** (8am-10pm, 7 days a week)  
**Malta** : +356 2395 2000  
**Cyprus** : +357 2240 5611

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

#### Physical hazards

Based on available data, the classification criteria are not met

#### Health hazards

Acute oral toxicity

Category 3 (H301)

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Respiratory Sensitization	Category 1 (H334)
Skin Sensitization	Category 1 (H317)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 1A (H350i)
Reproductive Toxicity	Category 1B (H360D)
Specific target organ toxicity - (single exposure)	Category 3 (H335)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)
<b>Environmental hazards</b>	
Acute aquatic toxicity	Category 1 (H400)
Chronic aquatic toxicity	Category 1 (H410)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 - May cause respiratory irritation
- H341 - Suspected of causing genetic defects
- H350i - May cause cancer by inhalation
- H360D - May damage the unborn child
- H372 - Causes damage to organs through prolonged or repeated exposure
- H410 - Very toxic to aquatic life with long lasting effects
- H301 + H331 - Toxic if swallowed or if inhaled

## Precautionary Statements

- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P311 - Call a POISON CENTER or doctor/physician
- P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
- P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
- P337 + P313 - If eye irritation persists: Get medical advice/attention

## Additional EU labelling

Restricted to professional users

## 2.3. Other hazards

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Toxic to terrestrial vertebrates  
This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Phosphinic acid, sodium salt, monohydrate	10039-56-2		25.0	-
Nickel(II) chloride	7718-54-9	EEC No. 231-743-0	25.0	Acute Tox. 3 (H301) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 1A (H350i) Repr. 1B (H360D) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Butanedioic acid, disodium salt	150-90-3	EEC No. 205-778-7	25.0	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)
Water	7732-18-5	231-791-2	24.9	-
Hydrogen fluoride	7664-39-3	EEC No. 231-634-8	0.1	Met. Corr. 1 (H290) Acute Tox. 2 (H300) Acute Tox. 1 (H310) Acute Tox. 2 (H330) Skin Corr. 1A (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Nickel(II) chloride	Skin Irrit. 2 (H315) :: C>=20% Skin Sens. 1 (H317) :: C>=0.01% STOT RE 1 (H372) :: C>=1% STOT RE 2 (H373) :: 0.1%<C<1%	1 (acute) 1 (chronic)	-
Hydrogen fluoride	Skin Corr. 1A :: C>=7% Skin Corr. 1B :: 1%<=C<7% Eye Irrit. 2 :: 0.1%<=C<1%	-	-

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

<b>Ingestion</b>	Do NOT induce vomiting. Call a physician or poison control center immediately.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

## **4.2. Most important symptoms and effects, both acute and delayed**

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

## **4.3. Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

#### **Suitable Extinguishing Media**

Carbon dioxide (CO<sub>2</sub>). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

#### **Extinguishing media which must not be used for safety reasons**

No information available.

### **5.2. Special hazards arising from the substance or mixture**

None reasonably foreseeable. Do not allow run-off from fire-fighting to enter drains or water courses.

#### **Hazardous Combustion Products**

Hydrogen chloride, Hydrogen fluoride, Oxides of phosphorus, Sodium oxides, Nickel oxides.

### **5.3. Advice for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

### **6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment.

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

## 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

## 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

**Technical Rules for Hazardous Substances (TRGS) 510**      Class 6.1D  
**Storage Class (LGK) (Germany)**

### 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Nickel(II) chloride	STEL: 0.3 mg/m <sup>3</sup> 15 min TWA: 0.1 mg/m <sup>3</sup> 8 hr Skin		
Hydrogen fluoride	STEL: 3 ppm 15 min STEL: 2.5 mg/m <sup>3</sup> 15 min TWA: 1.8 ppm 8 hr TWA: 1.5 mg/m <sup>3</sup> 8 hr	TWA: 1.8 ppm (8h) TWA: 1.5 mg/m <sup>3</sup> (8h) STEL: 3 ppm (15min) STEL: 2.5 mg/m <sup>3</sup> (15min)	TWA: 1.5 mg/m <sup>3</sup> 8 hr. TWA: 1.8 ppm 8 hr. F STEL: 2.5 mg/m <sup>3</sup> 15 min STEL: 3 ppm 15 min Skin

#### **Biological limit values**

List source(s):

**Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)**

ALFAA44070

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Hydrogen fluoride 7664-39-3 ( 0.1 )		0.01 mg/kg/ bw/day		0.01 mg/kg bw/day

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Butanedioic acid, disodium salt 150-90-3 ( 25.0 )				DNEL = 11.7mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Butanedioic acid, disodium salt 150-90-3 ( 25.0 )				DNEL = 41.1mg/m <sup>3</sup>
Hydrogen fluoride 7664-39-3 ( 0.1 )	DNEL = 2.5mg/m <sup>3</sup>	DNEL = 2.5mg/m <sup>3</sup>	DNEL = 1.5µg/m <sup>3</sup>	DNEL = 1.5mg/m <sup>3</sup>

## Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Nickel(II) chloride 7718-54-9 ( 25.0 )	PNEC = 0.3136µg/L		PNEC = 3.136µg/L		
Butanedioic acid, disodium salt 150-90-3 ( 25.0 )	PNEC = 0.1mg/L	PNEC = 0.48mg/kg sediment dw	PNEC = 1mg/L		PNEC = 37.2µg/kg soil dw
Hydrogen fluoride 7664-39-3 ( 0.1 )	PNEC = 0.9mg/L			PNEC = 51mg/L	PNEC = 11mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Butanedioic acid, disodium salt 150-90-3 ( 25.0 )	PNEC = 10µg/L	PNEC = 48µg/kg sediment dw	PNEC = 0.1mg/L		
Hydrogen fluoride 7664-39-3 ( 0.1 )	PNEC = 0.9mg/L				

## 8.2. Exposure controls

### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Nitrile rubber				
Neoprene				
PVC				

#### Skin and body protection

Long sleeved clothing.

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.  
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

## Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

## Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** Multi-purpose/ABEK conforming to EN14387 Particulates filter conforming to EN 143

## Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Particle filtering: EN149:2001

When RPE is used a face piece Fit Test should be conducted

## Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	<b>Method -</b> No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	<b>log Pow</b>	
Butanedioic acid, disodium salt	<-0.59	
Hydrogen fluoride	-1.4	
Vapor Pressure	23 hPa @ 20 °C	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

## 9.2. Other information

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

None known, based on information available

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

##### Hazardous Polymerization

No information available.

##### Hazardous Reactions

None under normal processing.

#### 10.4. Conditions to avoid

Incompatible products. Excess heat.

#### 10.5. Incompatible materials

Oxidizing agent.

#### 10.6. Hazardous decomposition products

Hydrogen chloride. Hydrogen fluoride. Oxides of phosphorus. Sodium oxides. Nickel oxides.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Product Information

##### (a) acute toxicity;

Oral	Category 3
Dermal	No data available
Inhalation	Category 3

##### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phosphinic acid, sodium salt, monohydrate	LD50 = 7640 mg/kg ( Rat )	-	-
Nickel(II) chloride	LD50 = 175 mg/kg ( Rat )	-	-
Water	-	-	-
Hydrogen fluoride	-	-	LC50 = 0.79 mg/L ( Rat ) 1 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

##### (d) respiratory or skin sensitization;

Respiratory	Category 1
Skin	Category 1



# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

May cause sensitization by skin contact

**(e) germ cell mutagenicity;** Category 2

**(f) carcinogenicity;** Category 1A

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Nickel(II) chloride	Carc Cat. 1A		Cat. 1	Group 1

**(g) reproductive toxicity;** Category 1B

**(h) STOT-single exposure;** Category 3

**Results / Target organs** Respiratory system.

**(i) STOT-repeated exposure;** Category 1

**Route of exposure** Inhalation  
**Target Organs** Lungs.

**(j) aspiration hazard;** No data available

**Symptoms / effects, both acute and delayed** Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Nickel(II) chloride	LC50: = 6.9 mg/L, 96h static (Cyprinus carpio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: > 100 mg/L, 96h static (Brachydanio rerio) LC50: 2.83 - 5.99 mg/L, 96h static (Poecilia reticulata) LC50: 29.76 - 43.57 mg/L, 96h semi-static (Poecilia reticulata) LC50: = 9.65 mg/L, 96h flow-through (Poecilia reticulata) LC50: = 25 mg/L, 96h flow-through (Pimephales promelas) LC50: 2.02 - 6.88 mg/L, 96h static (Pimephales promelas)	EC50: = 0.51 mg/L, 48h Static (Daphnia magna) EC50: = 6.68 mg/L, 48h (Daphnia magna)	EC50: 0.0063 - 0.0125 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 0.66 mg/L, 72h (Pseudokirchneriella subcapitata)

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

	LC50: 1.9 - 4 mg/L, 96h (Pimephales promelas) LC50: 6.63 - 9.15 mg/L, 96h static (Oncorhynchus mykiss) LC50: 6.7 - 9.7 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 2.02 - 6.88 mg/L, 96h static (Lepomis macrochirus) LC50: 18.1 - 25.5 mg/L, 96h flow-through (Lepomis macrochirus)		
Hydrogen fluoride	LC50 = 660 mg/L, 48h (Leuciscus idus)	EC50 = 270 mg/L, 48h (Daphnia species)	

Component	Microtox	M-Factor
Nickel(II) chloride		1 (acute) 1 (chronic)

**12.2. Persistence and degradability** Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary based on information available, May persist.  
**Persistence**  
**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**12.3. Bioaccumulative potential** May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Butanedioic acid, disodium salt	<-0.59	No data available
Hydrogen fluoride	-1.4	No data available

**12.4. Mobility in soil** The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

**12.5. Results of PBT and vPvB assessment** No data available for assessment.

**12.6. Endocrine disrupting properties**  
**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**12.7. Other adverse effects**  
**Persistent Organic Pollutant** This product does not contain any known or suspected substance  
**Ozone Depletion Potential** This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

**13.1. Waste treatment methods**

**Waste from Residues/Unused Products** Should not be released into the environment. Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point.

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information** Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not let this chemical enter the environment.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**14.1. UN number** UN3082  
**14.2. UN proper shipping name** Environmentally hazardous substances, liquid, n.o.s.  
**14.3. Transport hazard class(es)** 9  
**14.4. Packing group** III

### ADR

**14.1. UN number** UN3082  
**14.2. UN proper shipping name** Environmentally hazardous substances, liquid, n.o.s.  
**14.3. Transport hazard class(es)** 9  
**14.4. Packing group** III

### IATA

**14.1. UN number** UN3082  
**14.2. UN proper shipping name** Environmentally hazardous substances, liquid, n.o.s.  
**14.3. Transport hazard class(es)** 9  
**14.4. Packing group** III

**14.5. Environmental hazards** Dangerous for the environment  
Product is a marine pollutant according to the criteria set by IMDG/IMO

**14.6. Special precautions for user** No special precautions required.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Phosphinic acid, sodium salt, monohydrate	10039-56-2	-	-	-	X	X	-	X	X
Nickel(II) chloride	7718-54-9	231-743-0	-	-	X	X	KE-25837	X	X
Butanedioic acid, disodium salt	150-90-3	205-778-7	-	-	X	X	KE-12377	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Hydrogen fluoride	7664-39-3	231-634-8	-	-	X	X	KE-20198	X	X

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Phosphinic acid, sodium salt, monohydrate	10039-56-2	-	-	-	-	X	X	X
Nickel(II) chloride	7718-54-9	X	ACTIVE	X	-	X	X	X
Butanedioic acid, disodium salt	150-90-3	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Hydrogen fluoride	7664-39-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Phosphinic acid, sodium salt, monohydrate	10039-56-2	-	-	-
Nickel(II) chloride	7718-54-9	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 30. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details) Use restricted. See entry 27. (see link for restriction details)	-
Butanedioic acid, disodium salt	150-90-3	-	-	-
Water	7732-18-5	-	-	-
Hydrogen fluoride	7664-39-3	-	Use restricted. See entry 75. (see link for restriction details)	-

### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Phosphinic acid, sodium salt, monohydrate	10039-56-2	Not applicable	Not applicable
Nickel(II) chloride	7718-54-9	Not applicable	Not applicable
Butanedioic acid, disodium salt	150-90-3	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable
Hydrogen fluoride	7664-39-3	Not applicable	Not applicable

### Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Phosphinic acid, sodium salt, monohydrate	WGK2	
Nickel(II) chloride	WGK3	
Butanedioic acid, disodium salt	WGK1	
Hydrogen fluoride	WGK2	

Component	France - INRS (Tables of occupational diseases)
Nickel(II) chloride	Tableaux des maladies professionnelles (TMP) - RG 37, RG 37bis
Hydrogen fluoride	Tableaux des maladies professionnelles (TMP) - RG 32

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Hydrogen fluoride 7664-39-3 ( 0.1 )	Prohibited and Restricted Substances		

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H290 - May be corrosive to metals

H300 - Fatal if swallowed

H301 - Toxic if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H330 - Fatal if inhaled

H331 - Toxic if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

# SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

H341 - Suspected of causing genetic defects  
H350 - May cause cancer  
H350i - May cause cancer by inhalation  
H360D - May damage the unborn child  
H372 - Causes damage to organs through prolonged or repeated exposure  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

## Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/MDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

**Prepared By** Health, Safety and Environmental Department

**Revision Date** 30-Nov-2024

**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

# **SAFETY DATA SHEET**

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

---

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**