

Creation Date 29-Jan-2015

Revision Date 25-Jan-2024

Revision Number 4

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description:	<b>n-Butyl acrylate</b>
Cat No. :	<b>L03476</b>
Synonyms	2-Propenoic acid butyl ester
Index No	607-062-00-3
CAS No	141-32-2
EC No	205-480-7
Molecular Formula	C7 H12 O2
REACH registration number	-

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

### 1.3. Details of the supplier of the safety data sheet

Company	Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific) Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608
---------	--

E-mail address	begel.sdsdesk@thermofisher.com
----------------	--------------------------------

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

Flammable liquids	Category 3 (H226)
<b><u>Health hazards</u></b>	
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Skin Sensitization	Category 1 (H317)
Specific target organ toxicity - (single exposure)	Category 3 (H335)
<b><u>Environmental hazards</u></b>	
Chronic aquatic toxicity	Category 3 (H412)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Warning

### Hazard Statements

H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H412 - Harmful to aquatic life with long lasting effects

### Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER or doctor if you feel unwell

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)  
Lachrymator (substance which increases the flow of tears)  
Stench  
Toxic to terrestrial vertebrates  
This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

## 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Butyl acrylate	141-32-2	EEC No. 205-480-7	> 99	Flam. Liq. 3 (H226) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335) Aquatic Chronic 3 (H412)
4-Methoxyphenol	150-76-5	EEC No. 205-769-8	0.001-0.002	Acute Tox. 4 (H302) Skin Sens. 1 (H317) Eye Irrit. 2 (H319)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Butyl acrylate	STOT SE 3 (H335) :: C>=10%	-	-

REACH registration number	-
---------------------------	---

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Get medical attention. Wash off immediately with plenty of water for at least 15 minutes.
<b>Ingestion</b>	Do NOT induce vomiting. Get medical attention.
<b>Inhalation</b>	Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

### 5.2. Special hazards arising from the substance or mixture

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air.

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.

### 6.2. Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological Information. Collect spillage. Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Use only non-sparking tools.

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

**Technical Rules for Hazardous Substances (TRGS) 510**  
**Storage Class (LGK) (Germany)**

Class 3

### 7.3. Specific end use(s)

Use in laboratories

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Butyl acrylate	STEL: 5 ppm 15 min STEL: 26 mg/m <sup>3</sup> 15 min TWA: 1 ppm 8 hr TWA: 5 mg/m <sup>3</sup> 8 hr	TWA: 2 ppm (8h) TWA: 11 mg/m <sup>3</sup> (8h) STEL: 10 ppm (15min) STEL: 53 mg/m <sup>3</sup> (15min)	TWA: 2 ppm 8 hr. TWA: 11 mg/m <sup>3</sup> 8 hr. STEL: 10 ppm 15 min STEL: 53 mg/m <sup>3</sup> 15 min
4-Methoxyphenol			TWA: 5 mg/m <sup>3</sup> 8 hr. STEL: 15 mg/m <sup>3</sup> 15 min

#### Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Butyl acrylate 141-32-2 ( > 99 )			DNEL = 11mg/m <sup>3</sup>	
4-Methoxyphenol 150-76-5 ( 0.001-0.002 )				DNEL = 3mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Butyl acrylate 141-32-2 ( > 99 )	PNEC = 0.00272mg/L	PNEC = 0.0338mg/kg sediment dw	PNEC = 0.011mg/L	PNEC = 3.5mg/L	PNEC = 1mg/kg soil dw
4-Methoxyphenol 150-76-5 ( 0.001-0.002 )	PNEC = 0.0136mg/L	PNEC = 0.125mg/kg sediment dw		PNEC = 10mg/L	PNEC = 0.017mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Butyl acrylate 141-32-2 ( > 99 )	PNEC = 0.000272mg/L	PNEC = 0.00338mg/kg sediment dw			
4-Methoxyphenol 150-76-5 ( 0.001-0.002 )	PNEC = 0.00136mg/L	PNEC = 0.0125mg/kg sediment dw			

### 8.2. Exposure controls

#### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

**Hand Protection** Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Physical State</b>	Liquid	
<b>Appearance</b>	Colorless	
<b>Odor</b>	Stench	
<b>Odor Threshold</b>	No data available	
<b>Melting Point/Range</b>	-64 °C / -83.2 °F	
<b>Softening Point</b>	No data available	
<b>Boiling Point/Range</b>	145 °C / 293 °F	@ 760 mmHg
<b>Flammability (liquid)</b>	Flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 1.5 Vol% <b>Upper</b> 7.8 Vol%	
<b>Flash Point</b>	39 °C / 102.2 °F	<b>Method -</b> No information available
<b>Autoignition Temperature</b>	297 °C / 566.6 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	No information available	
<b>Viscosity</b>	0.869 mPa.s at 20 °C	
<b>Water Solubility</b>	1.4 g/l (20°C)	

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Butyl acrylate	2.38	
4-Methoxyphenol	1.3	
Vapor Pressure	5 mbar @ 20 °C	
Density / Specific Gravity	0.890	
Bulk Density	Not applicable	Liquid
Vapor Density	4.4	(Air = 1.0)
Particle characteristics	(liquid) Not applicable	

## 9.2. Other information

Molecular Formula	C7 H12 O2
Molecular Weight	128.17
Explosive Properties	explosive air/vapour mixtures possible
Self-accelerating polymerisation temperature (SAPT)	>50°C (all packages) Inhibitor level > 131 ppm

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Light sensitive.

### 10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization may occur upon depletion of inhibitor.
Hazardous Reactions	No information available.

### 10.4. Conditions to avoid

Temperatures above 30°C. Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure to light. Incompatible products.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Peroxides.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

#### (a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Butyl acrylate	LD50 = 3150 mg/kg ( Rat )	LD50 > 2 mg/kg ( Rabbit )	LC50 = 10.3 mg/L ( Rat ) 4 h
4-Methoxyphenol	1600 mg/kg (Rat)	LD50 > 2000 mg/kg ( Rabbit )	-

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

(b) skin corrosion/irritation;	Category 2
(c) serious eye damage/irritation;	Category 2
(d) respiratory or skin sensitization; Respiratory Skin	Based on available data, the classification criteria are not met Category 1  May cause sensitization by skin contact
(e) germ cell mutagenicity;	Based on available data, the classification criteria are not met
(f) carcinogenicity;	Based on available data, the classification criteria are not met  There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	Based on available data, the classification criteria are not met
(h) STOT-single exposure;  Results / Target organs	Category 3  Respiratory system.
(i) STOT-repeated exposure;  Target Organs	Based on available data, the classification criteria are not met  None known.
(j) aspiration hazard;	Based on available data, the classification criteria are not met
Symptoms / effects, both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

## 11.2. Information on other hazards

Endocrine Disrupting Properties	Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.
---------------------------------	---

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity effects

Toxic to aquatic organisms. Do not empty into drains. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Butyl acrylate	LC50: = 5.2 mg/L, 96h flow-through (Oncorhynchus mykiss)	EC50: = 8.2 mg/L, 48h (Daphnia magna)	EC50: = 5.5 mg/L, 96h (Pseudokirchneriella subcapitata)
4-Methoxyphenol	LC50: = 28.5 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 84.3 mg/L, 96h flow-through (Pimephales promelas)		

Component	Microtox	M-Factor
-----------	----------	----------



# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

Butyl acrylate	EC50 = 31.0 mg/L 30 min EC50 = 35.0 mg/L 15 min EC50 = 37.0 mg/L 5 min	
4-Methoxyphenol	EC50 = 3.66 mg/L 5 min EC50 = 4.30 mg/L 15 min EC50 = 4.61 mg/L 30 min	

**12.2. Persistence and degradability** Expected to be biodegradable  
**Persistence** Soluble in water, Persistence is unlikely, based on information available.  
**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**12.3. Bioaccumulative potential** Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Butyl acrylate	2.38	No data available
4-Methoxyphenol	1.3	No data available

**12.4. Mobility in soil** The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

**12.5. Results of PBT and vPvB assessment** Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

**12.6. Endocrine disrupting properties**  
**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**12.7. Other adverse effects**  
**Persistent Organic Pollutant** This product does not contain any known or suspected substance  
**Ozone Depletion Potential** This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information** Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**14.1. UN number** UN2348

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

**14.2. UN proper shipping name** BUTYL ACRYLATES, STABILIZED  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

## ADR

**14.1. UN number** UN2348  
**14.2. UN proper shipping name** BUTYL ACRYLATES, STABILIZED  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

## IATA

**14.1. UN number** UN2348  
**14.2. UN proper shipping name** BUTYL ACRYLATES, STABILIZED  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

**14.5. Environmental hazards** No hazards identified

**14.6. Special precautions for user** Inhibitors have been added to stabilize this product. Inhibitor levels should be maintained. Hazardous polymerization may occur upon depletion of inhibitor.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Butyl acrylate	141-32-2	205-480-7	-	-	X	X	KE-29450	X	X
4-Methoxyphenol	150-76-5	205-769-8	-	-	X	X	KE-23353	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Butyl acrylate	141-32-2	X	ACTIVE	X	-	X	X	X
4-Methoxyphenol	150-76-5	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Butyl acrylate	141-32-2	-	Use restricted. See item 75. (see link for restriction details)	-
4-Methoxyphenol	150-76-5	-	Use restricted. See item 75. (see link for restriction details)	-

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Butyl acrylate	141-32-2	Not applicable	Not applicable
4-Methoxyphenol	150-76-5	Not applicable	Not applicable

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Butyl acrylate	WGK1	Class I : 20 mg/m <sup>3</sup> (Massenkonzentration)
4-Methoxyphenol	WGK1	

Component	France - INRS (Tables of occupational diseases)
Butyl acrylate	Tableaux des maladies professionnelles (TMP) - RG 65
4-Methoxyphenol	Tableaux des maladies professionnelles (TMP) - RG 65

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

H302 - Harmful if swallowed

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

### Legend

# SAFETY DATA SHEET

n-Butyl acrylate

Revision Date 25-Jan-2024

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

**Prepared By**

Health, Safety and Environmental Department

**Creation Date**

29-Jan-2015

**Revision Date**

25-Jan-2024

**Revision Summary**

New emergency telephone response service provider.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**